



Protect what matters most.



www.PipeBurstPro.com

8 IN BUT LUG Spec Sheet

Actuator Features:

- Internal wire terminals
- Visual position indicator
- Manual override via hex key
- Indoor installation only

Actuator Specs:

- Voltage: 24VDC
- Enclosure Rating: NEMA 4/4x weather-proof (UL certified)
- Torque: 1,760 in/lbs
- Wiring:
 - Black Wire: power + to close, power – to open
 - Red Wire: power – to close, power + to open
 - Green Wire: common feedback
 - White Wire: closed feedback

Valve Features:

- Silicone free construction
- High performance
- One-piece body and self-centering disc
- Seat facing acts as flange gasket
- 3 shaft bushings support actuation
- Shaft sealing against external leakage

Valve Specs:

- Type: Butterfly Valve
- Size: 8 inch
- Connection: Lugged Flanged
- Body Material: Ductile Iron
- Disc Material: Stainless Steel
- Seats Material: EPDM
- Maximum Pressure: 150 PSI
- Operational Temperature Range: -22 to 230° F

Valve Installation:

- Position valve between flanges.
- Thread bolts into tapped holes from each side of the mounting flanges.



Total Assembly:

- Weight: 67 lbs

©2016 GreenField Direct, LLC rev.1.8.8.16



800.246.LEAK (5325)
info@greenfielddirect.com



Manufactured
in the U.S.A